



**Kemo Electronic GmbH**

Mato Vukovic  
 Leher Landstr. 20  
 27607 Geestland  
 Germany

Phone: +49 4743 9338-0  
 Fax: +49 4743 9338-22

http://www.kemo-electronic.de  
 email: info@kemo-electronic.de

HR.Nr. HRB 111 486  
 UstNr: DE 814 380 369

**FG016 - Exhaust Control**



If an exhaust hood is switched on with the window closed and a hearth is in use (oven, fireplace), it sucks toxic carbon monoxide gases from the fireplace into the room and may kill men and animals in the room. This exhaust control ensures that the exhaust hood (or other exhaust ventilators) may only be switched on if the window is in „tilt position“ or open.

The Fireplace Directive (M-FevVO§4) prohibits the operation of a fireplace and simultaneous suction of air, unless there is a sufficient fresh air supply (e.g. window in tilt position). The magnetic sensor of the exhaust control is fitted at the window. The exhaust hood can only be switched on if this transmits the signal “window open” via the approx. 5 m long cable. A back suction of dangerous flue gases into the living spaces is thus prevented. The exhaust control is an adapter plug, which is simply put between the socket and the plug of the exhaust hood.

**Technical Data:**

Switching capacity: (consumer maximally suitable for connection) 230 V/AC 1600 W

Fuse in the device: 8 - 10 A, 5 x 20 mm



Magnetic switch white dimensions: approx. 54 x 11 x 10 mm (is fixed at the window frame)

Magnet case white dimensions: approx. 54 x 11 x 10 mm (is fixed at the casement)

Cable length between the magnetic switch + adapter plug for the exhaust hood: approx. 5 m white

Adapter plug: (safety mains plug with safety socket) white

Dimensions: approx. 110 x 68 x 65 mm (measured without safety plug)



FG016

