7 November 2026

Kemo Electronic GmbH
Rolf Wittig
Leher Landstr. 20
27607 Geestland
Germany

Phone: +49 4743 9338-0
Fax: +49 4743 9338-22

http://www.kemo-electronic.de
email: info@kemo-electronic.de

HR.Nr. HRB 111 486
UstNr: DE 814 380 369

FG022 - Marten Repeller mobile





This mobile marten repellent operates with latest high-frequency technology (ultrasound) and without assembly work. This marten repellent may be employed everywhere (e.g. in cars, carports, garages and houses), ideal as protection for e.g. cars that are parked for longer periods. The optimum maintenance-free time of performance of 12 months can only be reached with high-quality alkaline manganese batteries (2 x 1.5 V Mignon AA, not enclosed). Of course, the device has to be mounted in such a way that no water or dirt may penetrate into the case. May also be used against mice and other rodents.



Technical Data:
Range of Action: > 55 m²
Frequency: approx. 24 kHz (± 15%)
Acoustic pressure: approx. 100 dB (± 20%) (Ultrasonic devices should have a sound pressure level exceeding 100 dB (C) to avoid habituation (ADAC test results). (Source de.wikipedia.org/wiki/Marderabwehr)
Operating voltage: 3 V/DC
Acoustic range: > 6 m

FG022

